

**CUSTOM ORTHODONTIC APPLIANCE FORMING METHOD AND APPARATUS**

Patent Number: WO9410935  
Publication date: 1994-05-26  
Inventor(s): ANDREIKO CRAIG A; PAYNE MARK A  
Applicant(s): ORMCO CORP [US]  
Requested Patent: AU5598894  
Application Number: WO1993US10858 19931109  
Priority Number (s): US19920973844 19921109; US19920973947 19921109; US19920973965 19921109; US19920973973 19921109  
IPC Classification: A61C7/00; A61C13/00  
EC Classification: A61C7/00, A61C7/14P, A61C7/20  
Equivalents: DE69327661D, DE69327661T, EP0667753 (WO9410935), B1, JP3380553B2, JP8508174T  
Cited Documents: EP0502227; WO9008512

**Abstract**

A system (10) and method by which an orthodontic appliance (25) is automatically designed and manufactured from digital lower jaw and tooth shape data (26) of a patient (14) provides for scanning, preferably from a model (20) of the patient's mouth, to produce two or three dimensional images, and digitizing contours and selected point on the patient's teeth and jaw. From the scanned individual patient data, a computer (30) constructs archforms and calculates finish tooth positions, then designs an appliance (25), preferably including archwires and brackets, to move the teeth to the calculated positions. Lower teeth are positioned at the gums on an arch defined by the lower jaw bone and modified to best fit the tooth tips on a smooth curve. Then upper archforms are derived from the lower archform. Crown long axes of the teeth are derived and optimally inclined in the treatment which places all lower teeth but the cusps in a plane and fits the occluding teeth to them. Overlaps for the upper incisors and cuspid rise are calculated. Brackets each have a base and an archwire support in which an archwire slot is to be cut to a custom inclination, depth, location and curvature, in a blank clamped to an inclinable holder, using a blade of a cutting machine (39). The holder and blade are moved by commands from a computer (30c). An archwire is automatically formed by a wire bender (40) into an optimize smooth arcuate shape and optimal low profile bracket design. Arch equations preferably start with a cubic spline equation and are converted to the form of a series of circle segments for machine control instructions for a numerically forming equipment. Placement jigs, simultaneously designed and automatically made with numerically controlled machinery (41) for positioning and orienting the appliance at connection points on the teeth, each have a surface custom shaped to the contour of a tooth. The machines (38-41) for making the brackets, wires and jigs are driven by commands derived from digitized tooth and jaw shape data and from digital representations of the tooth finish positions and appliance design.

Data supplied from the esp@cenet database - 12